M-W-F Spa Maintenance Program



Spa Maintenance Guide

Spa Breeze Line of Chemicals

Use the full line of Spa Breeze products to help keep your spa trouble-free

Product	Use	How Often?	
First Step	Prevents staining by dissolved metals in the water.	When filling spa	
Protect	Prevents mineral build-up on spa surfaces & equipment.	Weekly	
Brom 61 Tablets	Bromine Sanitizer.	Daily	
Brom Start	Bromine Amplifier.	When filling spa	
Chlor 62	Granular Chlorine Sanitizer.	Daily	
Refresh	Non-Chlorine Shock Treatment.	Weekly on the M-W-F Spa Maintenance Program	
Foam Away	Reduces excess foaming in spa.	Small amount as needed	
Scum Away	Treats build up of body oils, Weekly lotions, etc.		
Sparkle	Increases water clarity.	Weekly	
рH Up	Increases water pH.	As Needed	
pH Down	Decreases water pH		
Alkalinity Plus	Increases water alkalinity	As Needed	
Hardness Plus	Increases calcium hardness.	As Needed	
Filter Bright Spray	Cleans cartridge filter.	Weekly or as needed	
Filter Bright Soak	Deep cleans cartridge filter.	Monthly	
Multi Surface Care	Cleans hard cover & spa surface.	As Needed	

Introduction

Welcome to the Spa Breeze™ line of spa maintenance chemicals.

The maintenance of your new spa can be confusing. This is why Spa Breeze has created the weekly, simple to follow **M-W-F Spa Maintenance Program**. Following this program will help to keep your spa trouble-free.

There are a few things that Spa Breeze would like you to remember about spas before you begin. Though spas have been thought of as miniature swimming pools, their care differs from pools in several ways. The chemical balance of a swimming pool usually changes gradually, whereas in a spa the same changes can happen instantly.

Three major reasons are:

- The bather load in a spa is high. Four people in a 500-gallon spa have about the same effect on the water chemistry as 200 people have in a 20,000 gallon backyard swimming pool.
- The usual water temperature in a spa ranges between 98 and 104 degrees F. At these high temperatures the water evaporates at a rapid rate and leaves behind dissolved minerals and salts, most commonly referred to as total dissolved solids (TDS). TDS can hamper the work of the sanitizer and cause the water to take on a dull cast. In a spa, people perspire at the rate of approximately 1 pint for every 20 minutes. This adds to the TDS level and also contributes to the organic contamination.
- The water turn over rate is very rapid; together with aeration of jets and blowers it causes the sanitizer to dissolve more quickly.

Spa Breeze™ M-W-F Spa Maintenance Program is intended for residential customers only. Ask a spa professional for details on chemical requirements for use in other applications.

© 2011 QCA Spas, Inc. All rights reserved.

Safeguard Your Family

Spa Breeze[™] wants to ensure many happy experiences while using your new spa. Please take a moment to review these safety tips before using your spa.

- Always add chemicals to spa water, never water to chemicals.
- Add each chemical separately.
- Wait 15 minutes before adding any additional chemicals.
- Do not combine different chemicals before adding them to the spa water.
- Store chemicals according to the manufacturer's label and keep out of the reach of children.
- Maintain proper sanitation levels.
- Never heat your spa above 104° Fahrenheit
- Limit your spa session to 15 minutes.
- All users should shower without soap before entering the hot tub to remove excess deodorants, lotions, and body oils.
- Adult supervision must be present when children are using the spa.
- Do not consume alcohol while using the spa.
- If you are pregnant have high blood pressure or other cardiovascular condition, consult a physician before using the spa.
- All chemicals, if not handled properly, may be dangerous.

Getting Started

Depending on where you live, the water you use to fill your spa can be filled with many minerals and metals. These elements can affect which chemicals are needed to maintain proper water chemistry. Spa Breeze™ strongly recommends taking a water sample to a spa professional to determine the pH, calcium hardness, metals and total alkalinity of your water. Once this test has been completed you are ready to begin filling you spa for the first time.

Chemical Use Tips

When filling you spa, use a bottle of *First Step* to prevent staining and scaling on the spas surface.

Allow all chemicals to circulate in the spa for 15 minutes before adding additional Spa Breeze™ products.

Always Add Chemicals to Water, Never Water to Chemicals!



Phase 1: Filling the Spa

1. Fill the Spa with water.

The spa should be allowed to fill until the water level is at the center of the skimmer. If using a garden hose, allow it to run for several minutes to avoid introducing bacteria that may be living in the hose.

2. Add First Step to eliminate staining.

As the spa fills, add *First Step* to prevent build up of minerals on the spa surface. Add one bottle per 500 gallons of water. This should be allowed to circulate in a filled spa for 60 minutes before proceeding to Phase 2. A bottle of *First Step* is included in the Spa Breeze Starter Kit.





Phase 2: Water Balance

The phrase "Water Balance" refers to four interrelated factors:

pH- The measurement of relative acidity and basicity. The recommended range is 7.4-7.8. In this range both spa user and equipment are protected. If the pH levels are not in the acceptable range use the **pH Up** to make the water more basic or **pH Down** to make the water more acidic.



Alkalinity- Refers to the concentration of alkaline materials in the water. These materials have the ability to buffer or control the pH level. A range of 100-150 ppm should be kept at all times. Alkalinity is raised with Alkalinity Plus and reduced with pH Down.

Calcium Hardness- The measure of calcium salts contained in the water. The standard range of 175-225 ppm is recommended. Above this range the water can be cloudy and/or cause scaling on the tub surface, equipment, and piping. To increase hardness, add *Hardness Plus*. To reduce hardness, partially drain and refill spa.



Program Tip

Water pH and total alkalinity can be tested at home using the test strips included in your *Spa BreezeTM Starter Kit*. Calcium hardness should be determined by a spa professional.

Phase 3: Sanitizing the Spa

Spa Breeze™ offers two options in chemical sensitizers *Brom 61* bromine tablets or *Chlor 62* granular chlorine. Each method offers prevention and control of bacteria that can grow in the warm environment created by your spa.

Natural mineral purification can also be used to enhance the effects of bromine or chlorine such as Spa Mineral Cartridge or a professionally installed ozone system. While these items aid in sanitation, they are not a replacement for bromine or chlorine.



Brom 61

Place *Brom 61* Tablets in the chemical feeder. Then add 2 ounces of *Brom Start* directly to the water. Allow the spa to circulate until a bromine reading of 3-5 ppm is attained. Do not use your spa until you have obtained a 3-5 ppm reading. You may have to adjust the feeder to maintain a 3-5 ppm level. Check the bromine levels before each use to insure a proper reading. Check the feeder regularly to make sure there are enough tablets in the feeder. Refer to your feeder's directions for proper feeder adjustment.

Chlor 62

After your spa has been filled add 1 level tablespoon of chlorine to supershock the water and to establish a chlorine residual. Allow the spa to circulate until a chlorine reading of 1-3 ppm is attained. Do not use your spa until you have obtained a 1-3 ppm reading. At this time test the water again to ensure that the pH is between 7.4-7.8. If pH is below 7.4 add **pH Up** and if it is above 7.8 add **pH Down**.

NOTE: Frequent use, high temperature, and turbulent aerated water will require more frequent additions of the sanitizer system to maintain the 1-3 ppm level.

Ozone

Ozone is a gas created by an ozonator installed in a spa*. The ozonator creates natural ozone gas. This gas aids the bromine or chlorine in your system by destroying unwanted microbes. Ozone does not replace the need for bromine or chlorine but aids in the chemicals effectiveness. Follow the directions above for use of bromine or chlorine in your spa.



•Not all spas are equipped with an ozonator. Please ask your dealer if you have any questions.

Spa Mineral Cartridge

A mineral cartridge is placed in the filter cartridge of your spa. Over the next four months a balance of metallic ions is released to control bacterial growth. This system is safe to use with bromine, chlorine, and ozone systems. The mineral cartridge does not replace bromine or chlorine, but does aid in it's sanitizing capabilities and helps lower the ppm required to sanitize your spa water.

Shock

Oxidation is the process of removing organic materials such as body oils, cosmetics, and lotions from the water. When these organics increase in the water, the water becomes cloudy or hazy. Shocking with *Refresh* will oxidize the materials that may cause foul odors, eye or skin irritation, or dull, cloudy water. Shocking weekly will also increase the sanitizers' effectiveness.



Phase 4: Spa Breeze M-W-F Program

To maintain the chemical levels in your spa follow the **Spa Breeze M-W-F** Spa Maintenance Program. On the 2nd, 4th & 6th day of the week use the chart below to maintain safe chemical levels.

Chlorine Bromine

Test pH and total alkalinity Test chlorine

- Test pH and total alkalinity Adjust with pH Up or pH Down
- Adjust with **pH Up** or **pH Down**
 - Test bromine.

Add Chlor 62

Add Brom 61

Add Sparkle

Add Sparkle

- Test pH and total alkalinity
- Test pH and total alkalinity
- Adjust with **pH Up** or **pH Down**
 - Adjust with pH Up or pH Down

Test chlorine

Test bromine

Add **Protect**

- Add Protect
- Add Scum Away

- Add Scum Away
- Test pH and total alkalinity
- Test pH and total alkalinity
- Adjust with pH Up or pH Down
- Adjust with pH Up and pH Down

Test chlorine

- Test bromine
- Shock water with Refresh
- Shock water with Refresh



Program Tip

If you experience excess foaming, use Foam Away to quickly remove foam. Shocking your spa with Refresh will prevent much of the excess foaming.

Spa Breeze Recommendations

There is more to your spa then just the water. To ensure proper operation and extend the life of your spa please use these additional Spa Breeze™ products to maintain your spa.

Keep Your Spa Cartridge Filter Clean!

The cartridge filter does a big job by removing many of the body oils and minerals found in your spa water. With regular cleaning you can extend the life of the filter.

Filter Bright Spray: A spray-on-filter cleaner that can be used for a quick cleaning that removes surface containments.



Filter Bright Soak: An overnight treatment for a very clean filter.

Don't Forget the Hard Cover!

Use **Spa Breeze[™] Multi-Surface Care Cleaner** to remove dirt and oils from the hard cover.



Foam Troubles?

A build up of body oils, detergents, or lotions could be to blame for the excess foam in your spa. Add one squirt of *Foam Away*, approximately one-half of an ounce, as needed and the extra foam will disappear.



Troubleshooting Tips

Spa Breeze[™] offers a full line of spa maintenance products. Use the guide below to diagnose some common water problems. If you continue to have problems, consult your spa professional.

Symptom	Problem	Resolution	
	Low sanitizer chemical level	Shock spa with <i>Refresh</i> and check	
	or large amounts of microbial	chlorine/bromine level, adjust	
	growth.	accordingly.	
Cloudy Water	Build up of materials not able to be filtered.	Use <i>Sparkle</i> or add <i>Scum Away</i> .	
	Dirty filter, pH or total alkalinity is out of balance.	Use <i>Filter Bright</i> products to clean filter. Test water and use <i>pH Up</i> or <i>pH Down</i> as necessary.	
	High calcium levels.	Use <i>Protect</i> weekly	
White Scale/ Deposits	Mineral content of water is high.	Use <i>Protect</i> weekly. Test water and adjust as needed.	
Cloudy, Green Water	Low sanitizer chemical levels.	Shock with <i>Refresh</i> and check chlorine/bromine level, adjust accordingly.	
Clear Green Water	Copper or iron in spa water.	Add a bottle of <i>First Step</i> to neutralize minerals. Allow to circulate; check pH.	
Brown Water	Iron or manganese in spa water.	Add a bottle of <i>First Step</i> to neutralize minerals. Allow to circulate; check pH	
Odor	Large amounts of microbial growth.	Shock with <i>Refresh</i> and check chlorine/bromine level, adjust accordingly.	
Eye/Skin Irritation	Chloramines or excessive microbial growth.	Shock with <i>Refresh</i> and check chlorine/bromine level, adjust accordingly.	
	pH or alkalinity is out of balance.	Test water and use pH Up or pH Down as necessary.	
Scum Deposit on Waterline	Build-up of oils, lotions, or soaps	Use <i>Scum Away</i> weekly.	
	Build-up of oils, lotions, or detergents	Add <i>Foam Away</i> and shock with <i>Refresh</i> weekly.	
Excess Foam	Calcium levels are low.	Add <i>Hardness Plus</i> and test.	
	Large amount of total dissolved solids (TDS).	Levels should be 150-400 ppm. Drain spa. Refill using Phase 1 (page 5).	

Spa Terms Glossary

ppm - Parts per million. A measurement of the dissolved substance in the spa water such as bromine or chlorine.

pH - The measurement of relative acidity and basicity. The recommended range is 7.4 - 7.8. In this range both spa user and equipment are protected. If the pH levels are not in the acceptable range use pH Up to make the water more basic or pH Down to make the water more acidic.

Alkalinity - Refers to the concentration of alkaline materials in the water. These materials have the ability to buffer or control the pH level. A range of 100-150 ppm should be kept at all times. Alkalinity is raised with **Alkalinity Plus** and reduced with **pH Down**.

Calcium Hardness - The measure of calcium salts contained in the water. The standard range of 175-225 ppm is recommended. Above this range the water can be cloudy and/or cause scaling on the tub surface, equipment and piping. To increase hardness, add *Hardness Plus*. To reduce hardness, partially drain and refill with water.

TDS - (*Total Dissolved Solids*) refers to the dissolved solids found in water. Tap water, for instance, contains 50-330 ppm. If the level of TDS increases to 1500 ppm the effectiveness of spa sanitizing chemicals is greatly reduced and corrosion is accelerated. Spa Breeze recommends changing the water in your spa every three months.



Notes		

Notes		

Spa BreezeTM Chemical Maintenance for Spas

Brom 61 Tablets Chlor 62 Granular

Refresh

First Step

Protect

pH Up

pH Down

Hardness Plus

Alkalinity Plus

Filter Bright Spray & Soak

Multi Surface Care

Foam Away Scum Away Sparkle



1021 State Street, Bettendorf, IA 52722

DISCLAIMER: This product catalog is intended to help owners of home hot water spas/hot tubs keep their units clean, sanitized and safe for bathers. The guidelines herein are not intended for application to commercial spas/hot tubs. Spa water conditions, bather variations, and bather load will vary; accordingly, Spa Breeze and QCA Spas, Inc. do not warrant results and cannot be liable for personal injury or damage to spa shell surface, cabinetry, or equipment as a result of improper use of Spa Breeze chemicals. Spa Breeze and QCA Spas, Inc. will not be responsible for incidental or consequential damages or losses arising from any cause (e.g. water or chemical damage to carpet, floors, walls, ceiling, loss of use, etc. Spa Breeze and QCA Spas, Inc. reserve the right to change this Product Catalog, Spa Maintenance Guide, and Spa Breeze formulations, including the recommended guidelines without notice to the consumer. For the latest product information and recommendations see our Web site at www.qcaspas.com.

WARNING: Elderly persons, infants, and anyone subject to heart disease, diabetes, high or low blood pressure, strokes, epilepsy, or similar afflictions should not enter a spa alone or without consulting a physician. Unsupervised use by children should not be prohibited. Never use a spa while under the influence of alcohol, anti-coagulants, antihistamines, vasoconstrictors, vasodilators, stimulants, hypnotics, narcotics, or tranquilizers. If you are taking medication of any kind or being treated for any illness, consult your physician prior to the use of the spa. A spa should be kept at temperatures less than 104°F or 40°C for personal safety and health.